

New ALS3 Ventilation & Gas Safety Interlock Panel

ALS3 Features

- Power 2 single phase fans or monitor 2 three phase fans between 0.1A and 12A full load current.
- Current sensing of fans
- Digital display showing supply and extract fan running currents
- Simple push button set-up
- Fire alarm Input
- Onboard emergency stop and terminals for remote emergency stop
- 230V gas solenoid valve supply
- Gas proving -secondary 230V gas solenoid valve output with timed 'Dungs' pressure switch input
- 1 or 2 level alarm setting capability
- CO2 detector input and display
- Audible and visual display of alarms
- Tough IP66 ABS enclosure
- Wipe clean surface
- Volt free relay fault indication for BMS / Electric Heater Interlock

CO2 Displayed in PPM when used in conjunction with the NDIR wall mount CO2 detector.

Specifically designed for commercial kitchen safety.

Interlocks the Ventilation and Gas supply to kitchen appliances ensuring a safe working environment.

Designed to help with compliance to BS6173: 2009 & GSIUR: 1998



Neatafan Limited

Unit 12, Solent Industrial Estate,
Shamblehurst Lane,
Hedge End,
Southampton
SO30 2FX

Phone: 01489 783783

Fax: 01489 788048

E-mail: sales@neatafan.co.uk